New Crown RR Reach Truck from Goscor performs a dual role

RECENTLY Goscor Lift Truck Company (GLTC) was presented with a significant challenge by one of its clients - a packaging manufacturing concern in Cape Town.


The challenge was to provide a suitable machine for an application that demanded a reach truck capable of collecting large plastic bundles in roll-form (weighing in excess of 1,300kg, from the company's production line) then transporting these rolls to a roll store where they are stacked on a customdesigned racking system up to a height of 6,000mm. Stacking the rolls is a very intricate procedure, given the minimal space the operator has to work in.

Precision in the movement of the

forklift and its operator, as well as the accurate placement of the product, is the key to success.

GLTC's John Petrie recommended the appropriate machine for the demanding task at hand.

"The Crown RR Reach Truck, which has a lifting capacity of 2,000kg at the required lift height of 6,000mm, is ideal for the task," says Petrie. "Success is ensured through the aid of Crown's electronic steering system, which the operator directs by means of a multi-task control handle. The operator has a choice to sit or stand whilst driving, which aids his ability to get on and off. This, together with a set of locally designed and custom-built rotating



The Crown RR Reach Truck at work in a packaging manufacturing concern in Cape Town.

forks – which are manually adjustable – does just what is needed," he says.

The RR Reach

Truck is able to receive the large plastic rolls with its forks adjusted at a 45° angle, which allows the reach truck to scoop the product up where it sits firmly at the base of the angled forks, just in front of the carriage, for safe handling. The plastic rolls are manufactured in different sizes, so the ability to adjust the angled forks "inwards" or "outwards" according the products width is crucial.

Once the plastic rolls have been transported safely to the roll store, a cylindricalshaped metal sleeve is placed by the operator through the centre of the roll which protrudes either side. rotating forks are then adjusted to the standard position and locked in place. 150mm from the front tip of these forks, a recess/ groove has been cut away that allows the metal sleeve carrying the large roll to fit securely, before the load is lifted.

The operator then positions the reach

truck in front of the required rack, lifts the product to the exact required height, and is then able to gain access to the exact stacking position by means of a double-deep reach action, which is used to store the product away safely and securely. The forks can then be rotated from the 90° position to 0° position (normal fork type) to handle standard pallets. The rotation is manual and can be done easily by one

person in seconds.

"GLTC has provided a solution that enables the client to use a product that essentially performs a dual role – the role of a reach truck; and the role of a counter-balance truck – in challenging circumstances," concluded Petrie.